

# Digital Torque Wrench



- 應用於各種行業所需之螺絲鎖付 (機械、汽車、機車、航太、自行車...等)
- LCD 背光顯示
- 順時針及逆時針皆可操作
- 四種扭力單位·可供選擇切換：  
N-m, kgf-cm, lbf-in, lbf-ft
- 蜂鳴器、LED燈警示 (到達預設扭力值80%時)
- 震動警示 (到達預設扭力值90%時)
- 省電模式(2分鐘自動關機)
- 電池款: 使用AA電池x2 / 充電款: 使用Type-C充電線
- Apply for tightening nut(machine, car, motorcycle, airport, bike...etc.)
- LCD backlight display
- Both operator for cw, ccw
- 4 units change: N-m, kgf-cm, lbf-in, lbf-ft
- Warning function : Beep, LED indicator.  
(When reach the torque setting value 80%)
- Vibration function : When reach the torque setting value 90%.
- Automatically powers off when not in use for 2 minutes.
- Battery Type: AA x 2 batteries / Recharge Type: Type-C cable



■ 配件：收納用鐵製工具箱x1, 出廠校驗報告(符合ISO品質認證規範)x1, 說明書(中/英)x1, 電池款: AA電池x2, 充電款: Type-C 充電線

■ Content : Storage steel box x1, Certificate of calibration report x1, User guide(Bilingual) x1, Recharge Type: Type-C cable

## SPECIFICATIONS:

※Unit Conversion : 1 Nm = 10.2 kgf-cm = 0.738 lbf-ft = 8.851 lbf-in

產品編號 Item No.		精度 Accuracy	棘輪方頭 Drive	設定範圍 Setting Range	建議使用範圍 Suggested Range	解析度 Resolution	扳手長度 Length(mm)	扳手重量 Weight(±50g)		
電池款 Battery Type	充電款 Recharge Type									
WQ-30-1	WQ-30-1-C	CW:±1.5% CCW:±2.5%	1/4"	1.5~30 Nm	4.5~30 Nm	0.01 Nm	410	720		
WQ-30-2	WQ-30-2-C		3/8"	1.5~30 Nm	4.5~30 Nm		410	740		
WQ-60-2	WQ-60-2-C			3~60 Nm	9~60 Nm		410	740		
WQ-135-2	WQ-135-2-C			6.8~135 Nm	20~135 Nm	434	890			
WQ-135-3	WQ-135-3-C		1/2"	6.8~135 Nm	20~135 Nm	0.1 Nm	454	1080		
WQ-200-3	WQ-200-3-C				10~200 Nm		30~200 Nm	565	1300	
WQ-340-3	WQ-340-3-C				17~340 Nm		50~340 Nm	666	1420	
WQ-600-4	WQ-600-4-C			3/4"	60~600 Nm		90~600 Nm	940	3800	
WQ-800-4	WQ-800-4-C						80~800 Nm	120~800 Nm	1235	4800
WQ-1000-4	WQ-1000-4-C						100~1000 Nm	150~1000 Nm	1235	4800

註：精度的扭力範圍在最大操作值的20%~100%

Notes: Accuracy guaranteed at 20% to 100% of full scale.