

Digital Torque Adaptor



- 適用於任何傳統式棘輪扳手
 - LCD 背光顯示
 - 順時針及逆時針皆可操作
 - 四種扭力單位，可供選擇切換：N-m, kgf-cm, lbf-in, lbf-ft
 - 蜂鳴器、LED燈警示（到達預設扭力值80%時）
 - 省電模式(2分鐘自動關機)
 - 使用乙顆CR2032鋰電池
-
- Suit for any traditional ratchet wrench
 - LCD backlight display
 - Both operator for cw, ccw
 - 4 units change: N-m, kgf-cm, lbf-in, lbf-ft
 - Warning function : Beep, LED indicator.
(When reach the torque setting value 80%)
 - Automatically powers off when not in use for 2 minutes.
 - CR2032 battery



- 數位扭力轉接頭·接上一般或機械式棘輪扳手·即成為數位扭力扳手
- 配件：收納用鐵製工具箱x1, 出廠校驗報告(符合ISO品質認證規範)x1, 說明書(中/英)x1, CR2032鋰電池x1
- To connect any traditional ratchet wrench or hand socket wrench, it can be digital torque wrench.
- Content : Storage steel box x1, Certificate of calibration report (Using ISO specification) x1, User guide(Bilingual) x1, Mini screwdriver(replace the battery) x1

SPECIFICATIONS:

※Unit Conversion : 1 Nm = 10.2 kgf-cm = 0.738 lbf-ft = 8.851 lbf-in

產品編號 Item No.	精度 Accuracy	方頭 Driver	設定範圍 Setting Range	建議使用範圍 Suggested Range	解析度 Resolution	顯示器尺寸 Size(mm)	顯示器重量 Weight(g)
WS-60-2	CW:±1.5%	3/8"	3~60 Nm	9~60 Nm	0.01 Nm	75x42x39 (LxWxH)	189
WS-135-2			6.8~135 Nm	20~135 Nm			
WS-200-3	CCW:±2.5%	1/2"	10~200 Nm	30~200 Nm	0.1 Nm		
WS-340-3			17~340 Nm	50~340 Nm			

註：精度的扭力範圍在最大操作值的20%~100%

Notes: Accuracy guaranteed at 20% to 100% of full scale.