

## Digital Torque Wrench



- 應用於各種行業所需之螺絲鎖付  
(機械、汽車、機車、航太、自行車...等)
- LCD 背光顯示
- 順時針及逆時針皆可操作
- 四種扭力單位，可供選擇切換：  
N-m, kgf-cm, lbf-in, lbf-ft
- 蜂鳴器、LED燈警示 (到達預設扭力值80%時)
- 震動警示 (到達預設扭力值90%時)
- 省電模式(2分鐘自動關機)
- 使用AA電池\*2

- Apply for tightening nut(machine, car, motorcycle, airport, bike...etc.)
- LCD backlight display
- Both operator for cw, ccw
- 4 units change: N-m, kgf-cm, lbf-in, lbf-ft
- Warning function : Beep, LED indicator.  
(When reach the torque setting value 80%)
- Vibration function : When reach the torque setting value 90%.
- Automatically powers off when not in use for 2 minutes.
- AA x 2 battery



- 鎖固時·可量測旋轉多少角度的功能
- 配件：收納用鐵製工具箱x1, 出廠校驗報告(符合ISO品質認證規範)x1, 說明書(中/英)x1, AA電池x2
- Can measurement the degree after tighten the screw or nut.
- Content : Storage steel box x1, Certificate of calibration report (Using ISO specification) x1, User guide(Bilingual) x1

SPECIFICATIONS:

※Unit Conversion : 1 Nm = 10.2 kgf-cm = 0.738 lbf-ft = 8.851 lbf-in

產品編號 Item No.	精度 Accuracy	棘輪方頭 Driver	設定範圍 Setting Range	建議使用範圍 Suggested Range	解析度 Resolution	扳手長度 Length(mm)	扳手重量 Weight(±50g)
WA-30-1	CW:±1.5% CCW:±2.5%	1/4"	1.5~30 Nm / 0.1°~720°	4.5~30 Nm	0.01 Nm / 0.1°	410	720
WA-60-2		3/8"	3~60 Nm / 0.1°~720°	9~30 Nm		410	740
WA-135-2		1/2"	6.8~135 Nm / 0.1°~720°	20~135 Nm		0.1 Nm / 0.1°	434
WA-135-3			6.8~135 Nm / 0.1°~720°	20~135 Nm	454		1080
WA-200-3			10~200 Nm / 0.1°~720°	30~200 Nm	565		1300
WA-340-3			17~340 Nm / 0.1°~720°	50~340 Nm	666		1420
WA-600-4		3/4"	60~600 Nm / 0.1°~720°	90~600 Nm	940	3800	
WA-800-4			80~800 Nm / 0.1°~720°	120~800 Nm	1235	4800	
WA-1000-4			100~1000 Nm / 0.1°~720°	150~1000 Nm	150~1000 Nm	1235	4800

註：精度的扭力範圍在最大操作值的20%~100%

Notes: Accuracy guaranteed at 20% to 100% of full scale.