

# Digital Torque Adaptor



- 適用於任何傳統式棘輪扳手
- LCD 背光顯示
- 順時針及逆時針皆可操作
- 四種扭力單位，可供選擇切換：N-m, kgf-cm, lbf-in, lbf-ft
- 蜂鳴器、LED燈警示（到達預設扭力值80%時）
- 省電模式(2分鐘自動關機)
- WS系列，使用乙顆CR2032鋰電池。
- WS-A系列，使用AAA電池\*2

- Suit for any traditional ratchet wrench
- LCD backlight display
- Both operator for cw, ccw
- 4 units change: N-m, kgf-cm, lbf-in, lbf-ft
- Warning function : Beep, LED indicator.  
(When reach the torque setting value 80%)
- Automatically powers off when not in use for 2 minutes.
- WS series: CR2032 battery
- WS-A series: AAA x 2 battery



- 數位扭力轉接頭·接上一般或機械式棘輪扳手·即成為數位扭力扳手
- 鎖固時·可量測旋轉多少角度的功能
- 配件：收納用鐵製工具箱x1, 出廠校驗報告(符合ISO品質認證規範)x1, 說明書(中/英)x1, AAA電池x2, L型六角扳手(更換電池用)x1
- To connect any traditional ratchet wrench or hand socket wrench, it can be digital torque wrench.
- Can measurement the degree after tighten the screw or nut.
- Content : Storage steel box x1, Certificate of calibration report (Using ISO specification) x1, User guide(Bilingual) x1, L-type hex key wrench(replace the battery) x1

## SPECIFICATIONS:

※Unit Conversion : 1 Nm = 10.2 kgf-cm = 0.738 lbf-ft = 8.851 lbf-in

產品編號 Item No.	精度 Accuracy	方頭 Drive	設定範圍 Setting Range	建議使用範圍 Suggested Range	解析度 Resolution	顯示器尺寸 Size(mm)	顯示器重量 Weight(g)
WS-A135-2	CW:±1.5% CCW:±2.5%	3/8"	6.8~135 Nm / 0.1°~720°	20~135 Nm	0.1 Nm	75x50x39 (LxWxH)	210
WS-A200-3			10~200 Nm / 0.1°~720°	30~200 Nm			
WS-A340-3	1/2"	17~340 Nm / 0.1°~720°	50~340 Nm				

註：精度的扭力範圍在最大操作值的20%~100%

Notes: Accuracy guaranteed at 20% to 100% of full scale.