



材質與表面處理

- 固定座：尼龍(PA6+GF)，黑色。
- 手握柄：鋁合金(6063)，鋁本色。

特徵

- 固定座附螺絲孔蓋，外型美觀。
- 安裝迅速，從外向板面固定螺絲，板面可攻牙，或沖孔用螺母固定，而不受內部狹小影響作業。
- 固定座耐熱：-20°C~+150°C。
- 附M6螺絲。
- 耐酸鹼、耐油。

MATERIAL AND FINISH

- Holder: Nylon(PA6+GF), Black
- Handle: Aluminum alloy(6063), Anodized in natural color.

FEATURES

- Could be quick installed on the panel with a tapped hole or with a normal hole by nut.
- Tight the screw from outside, working space is not effected by the cabinet inner space.
- Weathering resistance of PA holder is -20°C~+150°C
- Holder attach a cover and M6*L25 screw, the outlook is artistic.
- Resistance to acid, alkali, greasiness.

SPECIFICATIONS

Unit:mm

| 產品編號 Item No. | 尺寸Dimensions | | | | 重量 Weight (g) | 荷重 Load capacity (kg/pcs) |
|------------------|--------------|-----|-----|-----|---------------------|------------------------------------|
| | L1 | L2 | L3 | P | | |
| EA-45120 | 80 | 142 | 100 | 120 | 61 | 53 |
| EA-45140 | 100 | 162 | 120 | 140 | 66 | 42 |
| EA-45170 | 130 | 192 | 150 | 170 | 76 | 38 |